

Tape Strong

Polyethylene adhesive tape with increased dimensional stability
Riwega | eternitycomfort

Technical data sheet
of: 12/07/2017
Art. 02040170-020401701-02040172
Rev.09 of: 31/10/2022



Properties	Tape Strong	Tape Strong 12/48	Tape Strong 200 X
Article	02040170	020401701	02040172
Measurements	60 mm x 25 m	60 mm x 25 m	200 mm x 25 m
Colour	Beige		
Adhesive	Solvent and emollient free acrylic based adhesive		
Adhesive backing	PP-Film (100 µm)		
Adhesive weight	210 g/m ² (DIN EN ISO 536)		
Reinforcement	PET mesh		
Thickness (without cover)	0,30 - 0,32 mm		
Pre-cut liner	-	12 + 48 mm x 25 m	100 + 100 mm x 25 m
Tear strength with elasticity	≥ 60 N/25 mm; 450% (DIN EN 14410)		
Application temperature	+5 °C / +30 °C (workable from -10 °C)		
Operating temperature	-30 °C / +100 °C		
Sd value	approx. 16 m		
Resistance to detachment	Passed (DIN 4108-11)		
Resistance to condensation	Very high		
Resistance to aging	Very high		
Initial adhesion (tack)	Very high		
UV stability	24 months*		
Packaging	10 rolls	10 rolls	2 rolls
Storage	Cool and dry away from UV rays, max.24 months		
Storage temperature	+18°C / +25°C		

* referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.