

VSK Clear Light

QUICK OVERVIEW: STRENGTHS

The self-adhesive vapour control layer, the lightest of the product group

- Vapour control layer, adhesive on the entire surface
- Ideal protection for walls, ceilings and pitched wooden roofs
- Transparent, with non slippery surface and pre-cut liner
- Great quality/price ratio



Composition:

- ① Anti-slip coating
- ② PP non-woven fabric
- ③ Acrylic dispersion-based adhesive
- ④ Pre-cutted liner 25 cm

Codes and measures

| Code | Code TOP SK | Width (m) | Length (m) | Pallet (m ²) |
|----------|-------------|-----------|------------|--------------------------|
| 02065055 | - | 1,5 | 50 | 1800 |

Features:



Classification:



Technical data sheet

| | | |
|---------------------------|------------------------|----------------------------|
| Material | PP.Anti-slip coating | |
| Film | Special Coating | |
| Colour | Semi-transparent white | |
| Mass per unit area | | 175 g/m ² |
| Glue weight | | 100 g/m ² |
| Pre-cutted liner | | 25 + 125 cm |
| Sd value | EN 1931 | 8 m |
| Water vapour permeability | EN ISO 12572 | ~ 3 g/m ² /24 h |
| Watern column | EN 20811 | npd** |
| Water tightness | EN 1928 (Met. A) | W1 |
| Tensile strength MD/CD* | EN 1931 | 115 / 80 N/50mm |
| Elongation MD/CD* | ISO 527-3 | 70 / 80 % |
| Tear resistance MD/CD* | EN 12310-1 | 60 / 80 N |
| Fire reaction class | EN ISO 11925-2 | E |
| UV stability | | 3 months |
| Temperature resistance | | -40°/+100°C |
| Working temperature | | -5°/+40°C |

*MD = longitudinal CD = transversal

**no performance determined

Riwega Srl is not responsible for negligent and improper use of its products