

Primer and solvents

63
R3



Primer Spray

Code	02040603
Material	synthetic rubber
Content	500 ml
Output (depending from surface)	~30 - 70 m (con L=60 mm)
Working temperature	-10°C / +30°C
Temperature resistance	-20°C / +80°C
Storage	dry, in the original can, max. 12 months



Primer Liquid

Code	02040600
Material	synthetic rubber and organic solvent
Content	500 ml
Output (depending from surface)	~150 - 250 ml/m ² (~3 m ²)
Viscosity	~150 mPa.s
Working temperature	+5°C / +30°C
Storage	dry, in the original can, max. 12 months



Primer Bitum

Code	02040601
Material	bitumen in water emulsion and additives
Content	5 l
Output (depending from surface)	~100 / 250 g/m ²
Viscosity	18 - 26 seconds
Density a 20°C	0,99 ± 1,05 kg/l
Drying time	20 - 40 minutes (23°C / 50%RH)
Working temperature	+5°C / +35°C
Storage	dry, in the original can, max. 12 months



Fire Zero Liquid (Fire Zero USB Accessories - page 56)

Code	02010342
Material	graphite water-based paint
Content	5 kg
Output	~5,6 kg/roll USB Fire Zero (~1,2 - 1,4 kg/m ²)
Mass density	1,22 ± 0,02 kg/l
Working temperature	+10°C / +35°C
Storage	dry, in the original can, max. 12 months